

Item	Specifications
Event tent	<p>52' x 85' Pole Tent with Aluminum Poles, Removable Sid-walls and Concrete Anchors.</p> <ol style="list-style-type: none"> <li>1. Fabric heavy duty 16 OZ./SQ YD. VINYL-laminated. Polyester, flame retardant. 3-PLY. 1000 denier, 9x9 weft-inserted wave. Fabric RF-Welded, sized to at least 90% tensile strength of fabric joined. -Where sewn stitching thread shall be UV-resistant polyester, manufactured for that purpose.</li> <li>2. Webbing shall be BE 2" wide polyester W/5000 LB MIN. Breaking strength (MAX. elongation at break = 12%). Mildew treated and UV-resistant.</li> <li>3. Poles shall 6061-T6, aluminum schedule 40 pipe. 10 Ft in length</li> <li>4. Guy straps shall be 2' wide ratchet strap with 10,000 LB. MIN. breaking strength, 3,333 working load limit. equipped to attach to concrete anchoring mechanism.</li> </ol> <p>Hardware shall be load rated.</p> <p>Side pole tabs and corner tabs shall be AISI 304 stainless steel.</p> <p>Center pole rings shall be AISI 304 stainless steel.</p> <p>Sid-walls shall be zipper type to be removed or rolled up for tent configuration and use.</p> <p>Concrete anchoring mechanism number, type and size necessary for holding power shall be determined based upon conditions and the design of the tent.</p>
Patio Shading	<p>Material: Aluminum</p> <p>Brand: FIM Umbrellas</p> <p>Shade Size: 9 Feet Wide</p> <p>Shape Type: Square</p> <p>Shade Color: Tan</p> <p>Pole Material: Aluminum Pole</p> <p>Lift System: Crank Lift</p> <p>Construction Quality: Commercial</p> <p>Dimensions: 9.5' x 9.5'</p> <p>Ribs: 8</p> <p>Umbrella With Ground Insert Base: 114 W x 114 D, 94 lbs</p> <p>Umbrella With Freestanding Offset Base: 114 W x 114 D, 98 lbs</p> <p>Umbrella With Deck Mount Plate: 114 W x 114 D, 105 lbs</p>